P6300 SERIES - GENERAL INFORMATION

VER. 10/25

	-	-	* N /
\sim	_	ı ⊢	· IV

Intel® Core® i5-1335U (4.6 GHz) Processor

Intel® Raptor Lake Chipset NVMe M.2 128 GB SSD Storage

8GB (exp. to 16 GB / 32 GB), Memory

1x DDR4 slot

 Video Card Integrated

 Audio Card HD Audio Codec WiFi Integrated module

MONITOR

 Panel 15" / 15,6" FHD / TFT, LED-backlit LCD

 Resolution 15" / 1024 x 768

15,6" FHD / 1920 x 1080

 Contrast Brightness 300 cd/m²

TOUCHSCREEN

 Type Capacitive Multitouch

EXTERNAL I/O PORTS

• USB 2x USB 3.0; 6x USB 2.0; 1x USB-C (reserved for power supply)

 Drawer 1x RJ12 (GPIO)

• LAN 1x Gbit LAN RJ-45 1x RS-232 RJ-45 Serial

 Audio 1x Line-out

POWER SUPPLY

 Power External 12V, 5A Type-C

Adapter

SUPPORTED OPERATING SYSTEMS

• Supported OS Windows 10/11 IoT Enterprise Windows 10/11 Pro

PHYSICAL CHARACTERISTICS

Certification

Operation / 0°C ~ 60°C Temperature Storage / -20°C ~ +80°C

10% ~ 90% non-condensing Humidity

 Colors Matte black

15" / 329 x 428 x 230 mm Dimensions $(W \times H \times D)$ 15,6" / 368 x 395 x 230 mm

15" / 4,9 kg Net Weight 15,6" / 5,5 kg

 Packaging and 15" / 5,4 kg accessories 15,6" / 6 kg

OPTIONS AND ACCESSORIES

16 GB / 32 GB SO-DIMM DDR4 Memory Storage NVMe SSD 256 GB / 512 GB / 1 TB

• USB keyboard Extended keyboard 105 keys QWERTY and mouse

> Mini keyboard 88 keys Italian version Compact industrial keyboard 82 keys with integrated touchpad QWERTY

Optical mouse with scroll

VFD (20 characters x 2 lines) Customer Display (CDP) Available in matte black

 Second 9.7" / LCD (1024 x 768) Monitor

9.7" / LCD touch screen (1024 x 768)

10.1" / LCD (1280 x 800) 13.3" / LCD (1920 x 1080) Available in matte black

Magnetic

ISO 7811 compliant, Stripe Reader supports track 1, 2, 3 (MSR)

 Smart Card Reader (SCR)

EMV level 1

• Dallas Reader iButton

 Fingerprint Reader

Dedicated module

100 x 100 mm

VESA Kit

All trademarks and registered trademarks belong to AP.esse S.p.A. or their respective owners. Product images and information are not binding and may be subject to change without prior notice.



AP.esse s.p.a. - Management and coordination Gruppo Buffetti S.p.a. / Via P. Mattarella, 32/30030 Gardigiano di Scorzè (VE) - Italy T +39 041 583 05 94 / F +39 041 583 05 95 / M info@apesse.com / W www.apesse.com P. IVA 02709990275 / Cap. Soc. 1.000.000€ i.v. / Reg. imp. di Venezia REA: 236495

BRANCH OFFICES

IT / Caserta - Catania / EU / Madrid - Düsseldorf

POS SYSTEM TOUCH SCREEN

P6400 PRIME SERIES









A DESIGN THAT CHARMS

POS SYSTEM TOUCH SCREEN **P6400 PRIME SERIES**

A STYLE THAT MAKES AN IMPACT

Display 15"

1024x768

Display 15,6"

1920x1080

tailored to meet the needs of retail and hospitality environments, with an elegant die-cast aluminium casing. The 15" narrow-bezel display, equipped with ultra-durable tempered glass and capacitive multi-touch technology, combines modern design with excellent readability performance.

enable the display to be fully folded, offering great installation versatility:

and maximum productivity even in the most demanding situations. Updates and

The wide range of I/O ports allows integration of all necessary peripherals to create







DISPLAYS AND ACCESSORIES FOR YOUR CUSTOMERS

The new P6400 Prime can integrate a VFD customer display and various types of LCD displays, including touchscreen versions, as well as smart card readers, magnetic card readers, and fingerprint scanners.

The 15" and 15.6" multi-touch displays offer a panoramic view and delivers sharp,

bright content.

