

P3200 SERIES - GENERAL INFORMATION

VER. 10/25

SYSTEM		PHYSICAL CHARACTERISTICS	
• Processor	Intel® N97 (3.6 GHz)	• Certification	CE
• Chipset	Intel® Alder Lake-N	• Temperature	Operation / 0°C - 60°C Storage / +20°C - +80°C
• Storage	SATA 3 (6 GB/s) 2.5" SSD 128GB, AHCI Support	• Humidity	10% - 90% senza condensazione
• Memory	8 GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (exp. to 16 GB)	• Colors	Anthracite grey matte / White matte
• Audio Card	HD Audio Codec	• Dimensions (W x H x D)	351 x 307 x 206 mm
MONITOR		OPTIONS AND ACCESSORIES	
• Panel	15" / TFT LCD, LED backlight	• Storage	2.5" SSD 128GB, HDD 500GB / 1 TB M.2 2242-D2-M (NVMe)
• Resolution	1024 x 768	• Customer Display (CDP)	VFD (20 characters x 2 lines)
• Contrast / Brightness	350 cd/m ²	• Second Monitor	9,7" / 15" / LCD (1024 x 768) 9,7" / 15" / LCD touch screen (1024 x 768) 10,1" / LCD (1280 x 800) 10,1" / LCD touch screen (1280 x 800) 15" / LCD touch screen (1024 x 768)
TOUCHSCREEN		• Magnetic Stripe Reader (MSR)	ISO 7811 compliance, supports tracks 1, 2, 3
• Type	Projective Capacitive Touch	• Smart Card Reader (SCR)	EMV level 1
EXTERNAL I/O PORTS		• Dallas Reader	iButton
• Video	1x MiniDP (with power out)	• Speaker	1 x 1 W (Mono)
• USB	6x (2x USB 3.0, 4x USB 2.0)	• VESA Kit	75x75mm, 100x100mm
• RS232	6x (COM1 with 5V/12V power out on pin 9, BIOS) (COM2-3 RJ-45, Full Signal) (COM4 RJ-11, TX/RX, 12V out, reserved for CDP) (COM5 Full Signal) (COM6 RJ-45, TX/RX, 5V power out, reserved for MSR)	• Serial Port Adapter Converter	From RJ-45 to D-sub 9 pin
• Cash Drawer	1x RJ-42, 6 pin (GPIO)	• Fingerprint Reader	Dedicated module
• LAN	1x Gigabit Ethernet, RJ-45	• TPM Module	Supported
• Audio	1x Line-out		
POWER SUPPLY			
• Power Adapter	External 12 V, 5 A		

All trademarks and registered trademarks belong to APasse S.p.A. or their respective owners. Product images and information are not binding and may be subject to change without prior notice.

POS SYSTEM TOUCH SCREEN P3200 SERIES

axon
MICRELEC
leading retail innovation



THE EVOLUTION OF THE SPECIES


POS SYSTEM TOUCH SCREEN P3200 SERIES

COMPACT, ELEGANT, EVER MORE PERFORMING

The P3200 POS system series guarantees excellent performance for the needs of retail and hospitality thanks to the 12th generation Intel® N97 processor that offers improved performance in terms of speed and security. The elegant and contemporary design promotes cooling and prevents dust deposits, ensuring maximum stability even in case of intensive and continuous use. The 15" touch screen display (4:3) offers high touch sensitivity, excellent visibility and industrial-grade scratch resistance (7H).

Immediate access to the communication ports and the removal of the disk facilitated by the exclusive slide mechanism makes maintenance and update operations even faster.

IDEAL FOR MARKET SECTORS



PROCESSOR



Intel® N97
(12a Gen.)

SUPPORTED OS



- Windows 10/11 Pro
- Windows 10 IoT LTSC 21
- Windows 11 IoT LTSC

MONITOR



Display 15"
1024x768

AVAILABLE IN



Anthracite grey
matte



White
matte

Immediate access to I/O ports allows immediate connection of peripherals and accessories

Quick access to SSD makes maintenance and upgrades easier

CUSTOMIZE YOUR POINT OF SALES

9.7" LCD courtesy display, also in touch screen version.

The customer display is also available in VFD version (2 Lines x 20 Characters)

Reinforced glass display with ultra-thin bezel

Sleek and contemporary design

The MSP magnetic reader is the ideal solution for speeding up various operations including:

- management of loyalty cards
- identification of employees
- authentication to reserved system functions

